



- |  |   |
|--|---|
| <p>① 10" ROUND GREEN PLASTIC VALVE BOX, CARSON-BROOKS 910 OR EQUAL</p> <p>② INSTALL BOX AT FINISH GRADE IN TURF AREAS, 2" ABOVE GRADE IN PLANTING AREAS</p> <p>③ QUICK COUPLER – SEE EQUIPMENT SCHEDULE (MOUNT 4 – 6" BELOW GRADE)</p> <p>④ 1" GALVANIZED RISER, LENGTH AS REQUIRED</p> <p>⑤ 6" MIN. DEPTH CLEAN PEA GRAVEL</p> <p>⑥ MAIN SUPPLY LINE</p> <p>⑦ SUB-GRADE COMPACTED TO 90% (TYP.)</p> | <p>⑧ 1" GALVANIZED DOUBLE ELBOW SWING JOINT</p> <p>⑨ 1" GALVANIZED NIPPLE, MIN. LENGTH 24" BEFORE TRANSITION TO PVC PIPE</p> <p>⑩ 1" BALL B11444 FORD VALVE</p> <p>⑪ SCH. 80 NIPPLE</p> <p>⑫ 2" SCH. 40 PVC SLEEVE NOTCHED OVER BALL VALVE</p> <p>⑬ 906L WEATHERMATIC LOCKING VALVE CAP PERMANENTLY ATTACHED TO SLEEVE. TOP OF MARKER 4" – 6" BELOW GRADE</p> |
|--|---|

NOTE: INSTALL (1) QUICK COUPLING VALVE AT ALL VALVES BANKS AS SHOWN ON PLANS.

QUICK COUPLING VALVE ASSEMBLY

***HYDE PARK CITY***

113 EAST CENTER  
HYDE PARK, UTAH 84318  
TEL: (435) 563-6507



***QUICK COUPLING  
VALVE ASSEMBLY***

IR-04

DATE: 02-09-21